

Adapter 1	Model A	
Operating Temperature	0 to 40 °C	32 to 100 °F
Storage Temperature	minus 10 to 40 °C	15 to 100 °F
Operating Pressure	0-10 kPa	0 to 1.5 Psi
Operating fluid	water, potable water, filtered water. Water may contain standard amounts of disinfectant.	
Maximum WCH (water column height) above the tap during operation	1 meter	40 inches
Flow Rate ^{1, 2, 3}	6 litres per minute @ 60 cm of WCH	1.6 gallons (US) per minute @ 24 inches of WCH
	2.4 litres per minute @ 10 cm of WCH	0.6 gallons (US) per minute @ 4 inches of WCH
Materials ⁴	Acetal or ABS, Rubber.	
Weight ¹	4 grams	0.15 ounce (US)
Connecting Thread	5/8"-18 and 3/4"-16	
Out of Vertical Installation Angle ^{1, 3} (maximum)	15°	
Overall Dimensions ¹ (maximum)	3.1 cm long, 2.2 cm wide with 1.9 cm hexagon	1.2 inch long, 0.9 inch wide with 3/4" hexagon
Compatibility	compatible with SaveAqua Tap Model A ⁵ . Reliance canisters with faucet having 1.9 - 2 cm (3/4 - 25/32") inside diameter of the outlet. Standard water cooler bottle lid.	
Recyclable	Check with your nearest recycling facility. Plastic parts can be recycled as code No. 9 or ABS or No. 7.	

¹ Approximate values.

² At approximately 20 °C (68 °F) water temperature.

³ Values provided with SaveAqua Tap Model A installed.

⁴ All parts are manufactured from FDA grade material after May of 2016.

⁵ Refer to Installation and Maintenance Instructions.

