

Adapter 2	Model A	
Operating Temperature	0 to 40 °C	32 to 100 °F
Storage Temperature	minus 10 to 40 °C	15 to 100 °F
Operating Pressure	0-10 kPa	0 to 1.5 Psi
Operating fluid	water, potable water, filtered water. Water may contain standard amounts of disinfectant.	
Maximum WCH (water column height) above the tap during operation	1 meter	40 inches
Flow Rate ^{1, 2, 3}	6 litres per minute @ 60 cm of WCH	1.6 gallons (US) per minute @ 24 inches of WCH
	2.4 litres per minute @ 10 cm of WCH	0.6 gallons (US) per minute @ 4 inches of WCH
Materials ⁴	Acetal or ABS.	
Weight ¹	4 grams	0.15 ounce (US)
Connecting Thread	5/8"-18	
Out of Vertical Installation Angle ^{1, 3} (maximum)	15°	
Overall Dimensions ¹ (maximum)	5.1 cm long, 1.9 cm diameter	2 inch long, 3/4" diameter
Compatibility	compatible with SaveAqua Tap Model A ⁵ . Flexible hose/tube with 1.3 cm (1/2") inside diameter.	
Recyclable	Check with your nearest recycling facility. Plastic parts can be recycled as code No. 9 or ABS or No. 7.	

¹Approximate values.

²At approximately 20 °C(68 °F) water temperature.

³Values provided with SaveAqua Tap Model A installed.

⁴All parts are manufactured from FDA grade material after May of 2016.

⁵Refer to Installation and Maintenance Instructions.

